

ZID-2010 R

-High-Resolution -IR-LED Fixed Lens Indoor Dome Camera

Features

- 1/3" Sony Super HAD High-Resolution Color CCD
- 600TVL High-resolution
- Built-in 4mm F2.0 Fixed Lens
- > Option: 6.0mm F2.0
- Auto Switching IR LED control by photocell
- > IR LED: 30pcs
- 3-Axis Gimbal Bracket
- Power: DC12V



Dimensions (unit:mm)



Specifications

| ITEM | ZID-2010 R |
|----------------------|---|
| Image Sensor | 1/3" Interline Transfer type Color CCD |
| Effective Pixels | NTSC: 768H x 494V (380K Pixels) / PAL: 752H x 582V (440 Pixels) |
| Scanning System | NTSC: 525 Lines 2:1 Interlace / PAL: 625 Lines 2:1 Interlace |
| Scanning Frequency | NTSC: 15.734KHz(H), 59.94Hz(V) / PAL: 15.625KHz(H), 50Hz(V) |
| Shutter Speed | NTSC: 1/60~1/100,000sec / PAL: 1/50~1/100,000sec |
| Resolution | 600TVL |
| S/N Ratio | More than 48dB (AGC Off) |
| Sync. System | Internal |
| White Balance | ATW |
| Min. Illumination | OLux (IR-LED On) |
| Lens | f= 4mm F2.0 Fixed Lens (Option: 6mm F2.0) |
| Video Output | VBS 1.0Vp-p (75ΩLoad) |
| Power Supply(*) | DC12V±10% |
| Power Consumption | Max.: 350mA/DC12V (IR-LED On) |
| Operating Temp. | -10°C~50°C |
| Operational Humidity | Max.: 90% RH |
| Dimension | 117mm(Ø) x 95mm(H) (Dome:Ø90) |

(*) Must use regulated & specified power supply.